



Optional bracket for street lighting or PTZ CCTV Camera

Rotatable outreach

Rotodrive- Outreach will not rotate without being driven by the mechanism.

Sealed for nil maintenance required in road/rail environment.

- Additional brake for redundancy fitted

- Stopper pins for limiting rotation range

- Height Range available: 5.5- 6.6m**
- 1, 2 road lane and railway configurations**
- Bi Directional rotation (Left and/or Right)**

Requirements

QTY Required _____

Post Construction



Lantern Height from Carriageway 5.5m 6.5m

Your Contact Details: _____

Post Material	Coating	
<input type="checkbox"/> Steel	<input type="checkbox"/> Galvanised	<input type="checkbox"/> Powder Coated
<input type="checkbox"/> Stainless Steel	<input type="checkbox"/> Raw - No Coating	<input type="checkbox"/> Painted

Lantern configuration

<input type="checkbox"/> Single Lantern 	<input type="checkbox"/> Dual Lanterns 	<input type="checkbox"/> Two Lane 	<input type="checkbox"/> Railway
---	--	---------------------------------------	--------------------------------------

Options



Improves safety by:

Gets staff off the mainline and away from catenary systems while performing maintenance works



Reduces cost by:

Not needing traffic control costs if outreach can safely be rotated to a non trafficable zone

Not needing to perform night works and incur penalty rates

Return form to: sales@rotopost.com.au or fax to: +61 7 3256 9960